




CODE WALL LED OUT

2 lighting sides



Material

aluminium - glass

Materiaal

aluminium - glas

Matériau

aluminium - verre



Finish

anodised aluminium - black - white
LED-holder : anodised aluminium
glass : transparent
lens : PMMA

Afwerking

geanodiseerd aluminium - zwart - wit
LED-houder : geanodiseerd aluminium
glas : transparant
lens : PMMA

Finition

aluminium anodisé - noir - blanc
LED-holder : aluminium anodisé
verre : transparent
lentille : PMMA

Lightsource

8 x power LED (included) 1.2W
cold white : 6000K - 880lm - CRI >75
8 x LED (included) 0.96W
warm white : 2700K - 912lm - CRI >93
beam : 10° - 25° - 40°

Lichtbron

8 x power LED (inclusief) 1.2W
koud wit : 6000K - 880lm - CRI >75
8 x LED (inclusief) 0.96W
warm wit : 2700K - 912lm - CRI >93
lichtbundel : 10° - 25° - 40°

Source lumineuse

8 x power LED (inclus) 1.2W
blanc froid : 6000K - 880lm - CRI >75
8 x LED (inclus) 0.96W
blanc chaud : 2700K - 912lm - CRI >93
rayon de lumière : 10° - 25° - 40°

Connection

350mA - driver excluded

Aansluiting

350mA - voeding exclusief

Connexion

350mA - convertisseur exclus

Specifications

outdoor
wall mounting
class III
IP55

Specificaties

buiten
wandmontage
klasse III
IP55

Spécifications

extérieur
applique
classe III
IP55

Accessories

LED driver max. 8 x 0.96W
to build in, not dimmable

Accessoires

LED voeding max. 8 x 0.96W
inbouw, niet dimbaar

Accessoires

LED convertisseur max. 8 x 0.96W
encastré, non-dimmable

cover plate : 80 x 80 mm
anodised aluminium - black - white

afdekplaat : 80 x 80 mm
geanodiseerd aluminium - zwart - wit

cache : 80 x 80 mm
aluminium anodisé - noir - blanc

