




## SCAR-LED 1FDS built-in 95



### Material

frame : aluminium  
flex : aluminium+metaal - silicone  
lens : PMMA

### Materiaal

frame : aluminium  
flex : aluminium+metaal - silicone  
lens : PMMA

### Matériau

structure : aluminium  
flex : aluminium+métal - silicone  
lentille : PMMA



### Finish

polished varnished - black - white  
flex : polished varnished - white or black silicone

### Afwerking

gepolijst en vernist - zwart - wit  
flex : gepolijst en vernist - witte of zwarte silicone

### Finition

poli et vernis - blanc - noir  
flex : poli et vernis - silicone blanc ou noir

### Lightsource

1 x power LED (included) 1.2W  
cold white : 6000K - 110lm - CRI >75  
1 x LED (included) 0.96W  
warm white : 2700K - 114lm - CRI >93  
beam : 10° - 25° - 40°

### Lichtbron

1 x power LED (inclusief) 1.2W  
koud wit : 6000K - 110lm - CRI >75  
1 x LED (inclusief) 0.96W  
warm wit : 2700K - 114lm - CRI >93  
lichtbundel : 10° - 25° - 40°

### Source lumineuse

1 x power LED (inclus) 1.2W  
blanc froid : 6000K - 110lm - CRI >75  
1 x LED (inclus) 0.96W  
blanc chaud : 2700K - 114lm - CRI >93  
rayon de lumière : 10° - 25° - 40°

### Connection

230V - driver included (to build in, not dimmable)

### Aansluiting

230V - voeding inclusief (inbouw, niet dimbaar)

### Connexion

230V - convertisseur inclus (encastré, non-dimmable)

### Specifications

indoor  
wall or ceiling mounting  
class I  
IP40

### Specificaties

binnen  
wand- of plafondmontage  
klasse I  
IP40

### Spécifications

intérieur  
applique ou plafonnier  
classe I  
IP40